

ITEM TECHNICAL CARD



hole diameter (mm)	3,3
d - rivet diameter	3,2
T - head width (mm)	6,0
L - rivet length (mm)	18,0
shear strength (N)	800
tensile strength (N)	1100
grip range (mm)	13,0 ÷ 15,0
body material	aluminium
mandrel material	steel
head type	countersunk

DESCRIZIONE \ DESCRIPTION: <b>AFS-Blind rivet Alu/Steel CSKH6,0 3,2x18,0</b>				CATEGORIA \ CATEGORY: <b>0016100.06000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT