



ITEM TECHNICAL CARD

h (mm)	24,0
Material	white zinc plated steel cl.8
Diameter	M24
pitch	2,0
UNI	7474
DIN	985
ISO	10511
m (mm)	15,0
S (mm)	36,0
Rules Description	hex nylon insert lock nuts, low type, fine thread

DESCRIZIONE \ DESCRIPTION: <b>Self-locking nylon ins. hex nut U7474/D985 fine cl.8 - white zinc plated</b>				CATEGORIA \ CATEGORY:		<b>00782ZB</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:			
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>			
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	<b>FASTENERS &amp; TOOLS</b> 
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	