



ITEM TECHNICAL CARD

length (mm)	38
Material	white zinc plated steel C15
Diameter	3,5
pitch	1,3
UNI	6955
DIN	7982C
ISO	7050
Rules Description	Phillips cross flat head tapping screws
r max (mm)	1,4
K (mm)	2,1
d1 (mm)	6,8
PH	2

DESCRIZIONE \ DESCRIPTION: <b>Phillips cross flat head tapping screw UNI 6955/DIN 7982 white zinc</b>				CATEGORIA \ CATEGORY:		<b>02297ZB.00500</b>	
MATERIALE \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:				
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>			
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	