


ITEM TECHNICAL CARD

s (mm)	4,0
length (mm)	80
Material	stainless steel A4
Diameter	M6
UNI	5933
DIN	7991
ISO	10642
D (mm)	12,0
k (mm)	3,3
t (mm)	2,5
Rules Description	hexagon socket countersunk head screws partially/fully threaded
pitch	1,0

DESCRIZIONE \ DESCRIPTION:		CATEGORIA \ CATEGORY:		0237700	
Hex socket countersunk head screw U5933/D7991 A4 - stainless steel					
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY:	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
<b>RIVIT</b>					
CONTROLLATO DA \ CHECKED BY:	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
<b>RIVIT</b>					
APPROVATO DA \ APPROVED BY:	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)
<b>RIVIT</b>					REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	