


ITEM TECHNICAL CARD

hole diameter (mm)	4,1
d - rivet diameter	4,0
T - head width (mm)	8,0
L - rivet length (mm)	9,0
k - head thickness (mm)	1,0
shear strength (N)	1200
tensile strength (N)	1700
grip range (mm)	3,0 ÷ 5,0
body material	aluminium
mandrel material	steel
head type	dome
RAL	RAL5013

DESCRIZIONE \ DESCRIPTION:					CATEGORIA \ CATEGORY:		0272400.07000		
AFT5013-Blind rivet Alu RAL5013/Steel DH 4,0x9,0									
MATERIAL \ MATERIAL:			TRATTAMENTO TERMICO \ HEAT TREATMENT:			NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY:		DATA:	TRATT. SUPERFICIALE\ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:				
RIVIT									
CONTROLLATO DA \ CHECKED BY:		DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]:			NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
RIVIT			HEAT TREATMENT (SURF) DEPTH [mm]:						
APPROVATO DA \ APPROVED BY:		DATA:	DUREZZA \ HARDNESS:	FOGLIO\ SHEET:	FORMATO FOGLIO:	A4	METODO 1 (ISO 128)	REVISIONE:	
RIVIT				1 OF 1	SHEET FORMAT:		METHOD 1 (ISO 128)	REVISION:	
			PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT				
					Mod.P023_07				



FASTENERS
& TOOLS



RIVIT.IT