

ITEM TECHNICAL CARD

length (mm)	50,0
Material	white zinc plated steel C15
Diameter	4,8
pitch	1,59
UNI	8117
DIN	7504K
ISO	15480
k (mm)	4,15
S (mm)	8,0
Rules Description	hex flat washer head self drilling screws
d1 (mm)	10,5

DESCRIZIONE \ DESCRIPTION: Hexagon flange head self-drilling screw UNI 8117/DIN 7504K white		CATEGORIA \ CATEGORY:		02909ZB.00200
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	
		PESO \ WEIGHT:	Scale \ SCALE:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
			CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION:



**FASTENERS
& TOOLS**
RIVIT.IT