




ITEM TECHNICAL CARD

| | |
|-------------------------|--------|
| setting torque (Nm) | 25,0 |
| hole diameter (mm) | 14,0 |
| model | RHAF08 |
| plug length (mm) | 50,0 |
| minimum hole depth (mm) | 65,0 |
| profondità posa (mm) | 50,0 |
| for screw | M8 |
| max grip range (mm) | 10,0 |
| max loading (daN) | 450,0 |

| | | | | | | |
|--|-------|--|---|---|---|--|
| DESCRIZIONE \ DESCRIPTION: RHA/F-Steel anchor only head h.14,0 M8x50 | | | CATEGORIA \ CATEGORY: | | 0364800.00050 | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | | |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: | |  | |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW | | | |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: 1 OF 1 | FORMATO FOGLIO: SHEET FORMAT: A4 | METODO 1 (ISO 128) METHOD 1 (ISO 128) | REVISIONE: REVISION: |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT Mod.P023_07 |  | FASTENERS & TOOLS  RIVIT.IT |