

ITEM TECHNICAL CARD




wrench (mm)	8
model	PTEFR48025
length (mm)	25
hole thickness (mm)	1,75 - 4,0
Material	white zinc plated steel C15
Diameter	4,8
UNI	8117
DIN	7504K
ISO	15480
Rules Description	hex flat washer head self drilling screws

DESCRIZIONE \ DESCRIPTION:

Hexagon flange head self-drilling screw UNI 8117/DIN 7504K white



CATEGORIA \ CATEGORY:

04843ZB.00500

MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:		 FASTENERS & TOOLS  RIVIT.IT
ESEGUITO DA \ DRAWN BY:	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:			
RIVIT						
CONTROLLATO DA \ CHECKED BY:	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
APPROVATO DA \ APPROVED BY:	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET:	FORMATO FOGLIO: SHEET FORMAT:	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:
RIVIT			1 OF 2	A4		
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07		

ITEM TECHNICAL CARD

N (mm)	10
D min/max (mm)	9,8/10,5
K min/max (mm)	4,15/4,45
sheet thickness (mm)	4
B min (mm)	0,9
d max (mm)	4
S min/max (mm)	7,78/8,0

DESCRIZIONE \ DESCRIPTION: Hexagon flange head self-drilling screw UNI 8117/DIN 7504K white				CATEGORIA \ CATEGORY: 04843ZB.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		 FASTENERS & TOOLS  RIVIT.IT
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 2 OF 2	FORMATO FOGLIO: SHEET FORMAT: A4	
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	