


ITEM TECHNICAL CARD

length (mm)	19,0
Material	white zinc plated steel C15
Diameter	4,2
pitch	1,41
UNI	8117
DIN	7504K
ISO	15480
k (mm)	4,0
S (mm)	7,0
Rules Description	hex flat washer head self drilling screws
d1 (mm)	8,8

DESCRIZIONE \ DESCRIPTION: <b>Hexagon flange head self-drilling screw UNI 8117/DIN 7504K white</b>		CATEGORIA \ CATEGORY: <b>04848ZB.01000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		FOGLIO \ SHEET: <b>1 OF 1</b>	REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:
		CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT