




ITEM TECHNICAL CARD

length (mm)	32,0
Material	black zinc plated steel C15
Diameter	4,2
pitch	1,4
UNI	8118
DIN	7504N
ISO	15481
k (mm)	3,05
Rules Description	Pozidriv cross recessed pan head self drilling screws
d1 (mm)	8,2
PH	2

DESCRIZIONE \ DESCRIPTION: Pan head Ph+ self-drilling screw UNI8118/DIN7504N C15 - black zinc			CATEGORIA \ CATEGORY: 04903ZN.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW	
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07
				METODO 1 (ISO 128) METHOD 1 (ISO 128)
				REVISIONE: REVISION:
				
 FASTENERS & TOOLS  RIVIT.IT				