



ITEM TECHNICAL CARD

length (mm)	22,0
Material	black zinc plated steel C15
Diameter	3,5
pitch	1,3
UNI	8119
DIN	7504P
ISO	15482
k (mm)	2,1
Rules Description	Phillips cross recessed flat head self-drilling screws
d1 (mm)	6,8
PH	2

DESCRIZIONE \ DESCRIPTION: <b>Csk flat head self drilling screw UNI8119/DIN7504P black zinc plated</b>		CATEGORIA \ CATEGORY:		<b>04927ZN.01000</b>
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>	
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
				METODO 1 (ISO 128) METHOD 1 (ISO 128)
				REVISIONE: REVISION:
				
				 <b>FASTENERS &amp; TOOLS</b> RIVIT.IT