


ITEM TECHNICAL CARD

length (mm)	25,0
Material	white zinc plated steel C15
Diameter	6,3
pitch	1,81
UNI	8117
DIN	7504K
ISO	15480
k (mm)	6,15
S (mm)	10,0
Rules Description	hex flat washer head self drilling screws
d1 (mm)	13,2

DESCRIZIONE \ DESCRIPTION: Hexagon flange head self-drilling screw U8117/D7504K h.6 max white				CATEGORIA \ CATEGORY: 04975ZB.02800	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT