

ITEM TECHNICAL CARD

d - wire dia (mm)	0,7
Ds - pin dia (mm)	5,0
Df - hole dia (mm)	3,6
Lo - free length (mm)	35,0
Fn - max. permissible load (kgf)	1,73
Ln - spring length (mm)	21,5
fn - spring deflection (mm)	13,5
Rg - spring rate (kgf/mm)	0,128

DESCRIZIONE \ DESCRIPTION: Compression spring C70 - white zinc plated steel CO.04/079				CATEGORIA \ CATEGORY: 0603500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION:



**FASTENERS
& TOOLS**
RIVIT.IT