



ITEM TECHNICAL CARD

d - wire dia (mm)	1,5
Ds - pin dia (mm)	9,3
Df - hole dia (mm)	6,3
Lo - free length (mm)	10,5
Fn - max. permissible load (kgf)	11,52
Ln - spring length (mm)	7,8
fn - spring deflection (mm)	2,7
Rg - spring rate (kgf/mm)	4,267

DESCRIZIONE \ DESCRIPTION: Compression spring C70 - white zinc plated steel CO.10/169				CATEGORIA \ CATEGORY:		0604100	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:				
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	FASTENERS & TOOLS  RIVIT.IT
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	