


ITEM TECHNICAL CARD

d - wire dia (mm)	0,9
Ds - pin dia (mm)	8,5
Df - hole dia (mm)	6,7
Lo - free length (mm)	38,0
Fn - max. permissible load (kgf)	3,49
Ln - spring length (mm)	19,3
fn - spring deflection (mm)	18,7
Rg - spring rate (kgf/mm)	0,186

DESCRIZIONE \ DESCRIPTION: Compression spring C70 - white zinc plated steel CO.11/062				CATEGORIA \ CATEGORY: 0604200	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT