

ITEM TECHNICAL CARD

d - wire dia (mm)	2,0
Ds - pin dia (mm)	16,8
Df - hole dia (mm)	12,8
Lo - free length (mm)	31,0
Fn - max. permissible load (kgf)	8,07
Ln - springh lenght (mm)	22,0
fn - spring deflection (mm)	9,0
Rg - spring rate (kgf/mm)	0,897

DESCRIZIONE \ DESCRIPTION:					CATEGORIA \ CATEGORY:		0606300									
Compression spring C70 - white zinc plated steel CO.32/191																
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:				NOTE \ NOTES:		 FASTENERS & TOOLS  RIVIT.IT								
ESEGUITO DA \ DRAWN BY: RIVIT		DATA:		TRATT. SUPERFICIALE\ SURF. TREATMENT:					Rugosità superficiale generale: General surface roughness:							
CONTROLLATO DA \ CHECKED BY: RIVIT		DATA:		PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW										
APPROVATO DA \ APPROVED BY: RIVIT		DATA:		DUREZZA \ HARDNESS:		FOGLIO\ SHEET: 1 OF 1			FORMATO FOGLIO: SHEET FORMAT:		A4		METODO 1 (ISO 128) METHOD 1 (ISO 128)		REVISIONE: REVISION:	
				PESO \ WEIGHT:		Scale \ SCALE:			CARTIGLIO \ FORMAT Mod.P023_07							