



ITEM TECHNICAL CARD

d - wire dia (mm)	1,6
Ds - pin dia (mm)	29,5
Df - hole dia (mm)	26,3
Lo - free length (mm)	13,0
Fn - max. permissible load (kgf)	0,65
Ln - spring length (mm)	10,3
fn - spring deflection (mm)	2,7
Rg - spring rate (kgf/mm)	0,241

DESCRIZIONE \ DESCRIPTION: Compression spring C70 - white zinc plated steel CO.44/198				CATEGORIA \ CATEGORY:		0607500		
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:		 FASTENERS & TOOLS  RIVIT.IT		
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:					
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW				
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)			REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	