



ITEM TECHNICAL CARD

d - wire dia (mm)	1,0
Lo - free length (mm)	26,0
Fn - max. permissible load (kgf)	5,11
Ln - spring length (mm)	41,25
fn - spring deflection (mm)	15,25
Rg - spring rate (kgf/mm)	0,3
De - spring outside dia (mm)	7,0
Fo - spring preload (kgf)	0,4

DESCRIZIONE \ DESCRIPTION: Tension spring C70 - white zinc plated steel TR.15/133				CATEGORIA \ CATEGORY:		0610000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:			
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		 FASTENERS & TOOLS RIVIT.IT	
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)		
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	