

ITEM TECHNICAL CARD

diámetro vite	M6
E (mm)	0,5
tipo	DGF4106C
A (mm)	14,0
C (mm)	6,0
B (mm)	12,4
s - spessore lamiera (mm)	0,9 - 1,0
D (mm)	20,4
foro lamiera (mm)	8,0x13,0

DESCRIZIONE \ DESCRIPTION:					CATEGORIA \ CATEGORY:		0762300.00250	
DG4106-C Dado FE Gab.c/Al.OX ss0,9-1,1 f 8,0x13 M6								
MATERIAL \ MATERIAL:			TRATTAMENTO TERMICO \ HEAT TREATMENT:				NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY:		DATA:	TRATT. SUPERFICIALE\ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:			
RIVIT								
CONTROLLATO DA \ CHECKED BY:		DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:			NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
RIVIT								
APPROVATO DA \ APPROVED BY:		DATA:	DUREZZA \ HARDNESS:	FOGLIO\ SHEET:	FORMATO FOGLIO:	A4	METODO 1 (ISO 128)	REVISIONE:
RIVIT				1 OF 1	SHEET FORMAT:		METHOD 1 (ISO 128)	REVISION:
			PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07			



FASTENERS
& TOOLS



RIVIT.IT