



ITEM TECHNICAL CARD

Material	white zinc plated steel cl.8
Diameter	M4
pitch	0,7
UNI	7473
DIN	982
ISO	7040
m (mm)	3,2
S (mm)	7,0
Rules Description	hex nylon insert lock nuts, high type
h (mm)	6,0

DESCRIZIONE \ DESCRIPTION: Self-locking nylon ins. hex nut U7473/D982 cl.8 - white zinc plated				CATEGORIA \ CATEGORY:		07650ZB.02000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:			
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)		
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	