




ITEM TECHNICAL CARD

| | |
|-------------------|---------------------------------------|
| Material | white zinc plated steel cl.8 |
| Diameter | M16 |
| pitch | 2,0 |
| UNI | 7473 |
| DIN | 982 |
| ISO | 7040 |
| m (mm) | 14,0 |
| S (mm) | 24,0 |
| Rules Description | hex nylon insert lock nuts, high type |
| h (mm) | 18,0 |

| | | | | | | | | |
|--|-------|--|--|---|---|---|--|-------------------------|
| DESCRIZIONE \ DESCRIPTION: Self-locking nylon ins. hex nut U7473/D982 cl.8 - white zinc plated | | | | CATEGORIA \ CATEGORY: | | 07658ZB.00100 | | |
| MATERIALE \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | |  FASTENERS & TOOLS  RIVIT.IT | | |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: | | | | | |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW | | | | | |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: 1 OF 1 | FORMATO FOGLIO: SHEET FORMAT: A4 | METODO 1 (ISO 128) METHOD 1 (ISO 128) | | | REVISIONE: REVISION: |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT Mod.P023_07 |  | | | |