


ITEM TECHNICAL CARD

length (mm)	40
Material	brass plated steel C15
Diameter	3,5
DIN	7505A
Rules Description	flat head chipboard screws
D min/max (mm)	6,64/7,00
K max (mm)	2
r1~ (mm)	1,8
b max (mm)	0,9
N Pozi Recess	2
recess m ~	4

DESCRIZIONE \ DESCRIPTION: <b>Flat head chipboard screw DIN 7505A brass plated steel C15 3,5x40</b>		CATEGORIA \ CATEGORY: <b>08743OT.00500</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		FOGLIO \ SHEET: <b>1 OF 1</b>	REVISIONE: REVISION:
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
		Scale \ SCALE:	



**FASTENERS  
& TOOLS**  
RIVIT.IT