


ITEM TECHNICAL CARD



hole diameter (mm)	3,5
d - rivet diameter	3,4
T - head width (mm)	7,0
L - rivet length (mm)	14,0
k - head thickness (mm)	0,9
shear strength (N)	1200
tensile strength (N)	1700
grip range (mm)	8,5 ÷ 10,5
body material	zinc coated copper
mandrel material	steel
head type	dome

DESCRIZIONE \ DESCRIPTION: <b>RZFT-Blind rivet Zinc plated Copper/Steel DH 3,4x14,0</b>		CATEGORIA \ CATEGORY: <b>1200800.00500</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FUOGGIO \ SHEET: <b>1 OF 1</b> FORMATO FOGGIO: <b>A4</b> SHEET FORMAT: <b>A4</b>
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b> Scale \ SCALE:
		 <b>FASTENERS &amp; TOOLS</b>  <b>RIVIT.IT</b>	