




ITEM TECHNICAL CARD

| | |
|-------------------|---|
| s (mm) | 10,0 |
| length (mm) | 30,0 |
| Material | stainless steel A2 |
| Diameter | M16 |
| UNI | 5933 |
| DIN | 7991 |
| ISO | 10642 |
| D (mm) | 30,0 |
| k (mm) | 7,5 |
| t (mm) | 5,3 |
| Rules Description | hexagon socket countersunk head screws partially/fully threaded |
| pitch | 2,0 |

| | | | | | |
|--|-------|---|---------------------------------|---|---|
| DESCRIZIONE \ DESCRIPTION: | | CATEGORIA \ CATEGORY: | | 1337900.00025 | |
| Hex socket countersunk head screw U5933/D7991 A2 - stainless steel | | | | | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | |
| ESEGUITO DA \ DRAWN BY: | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: |  | |
| RIVIT | | | General surface roughness: | | |
| CONTROLLATO DA \ CHECKED BY: | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: | NON SCALARE IL DISEGNO | |  |
| RIVIT | | HEAT TREATMENT (SURF) DEPTH [mm]: | DO NOT RESIZE THE DRAW | | |
| APPROVATO DA \ APPROVED BY: | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: | FORMATO FOGLIO: | METODO 1 (ISO 128) |
| RIVIT | | | 1 OF 1 | A4 | METHOD 1 (ISO 128) |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT | REVISIONE: REVISION: |
| | | | | Mod.P023_07 |  |