

ITEM TECHNICAL CARD

length (mm)	35
Material	yellow zinc plated steel C15
Diameter	6
DIN	7505A
Rules Description	flat head chipboard screws
D min/max (mm)	11,57/12,00
K max (mm)	3,35
r1~ (mm)	2,5
b max (mm)	1,75
N Pozi Recess	3
recess m ~	6,6

DESCRIZIONE \ DESCRIPTION: <b>Flat head chipboard screw DIN 7505A yellow zinc plated steel C15</b>		CATEGORIA \ CATEGORY:		<b>15249ZG</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	REVISIONE: REVISION:



**FASTENERS  
& TOOLS**  
RIVIT.IT