

ITEM TECHNICAL CARD

h (mm)	16,0
Material	white zinc plated steel cl.8
Diameter	M16
pitch	1,5
UNI	7474
DIN	985
ISO	10511
m (mm)	10,5
S (mm)	24,0
Rules Description	hex nylon insert lock nuts, low type, fine thread

DESCRIZIONE \ DESCRIPTION: Self-locking nylon ins. hex nut U7474/D985 fine cl.8 - white zinc plated				CATEGORIA \ CATEGORY: 16951ZB.00200	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION:



**FASTENERS
& TOOLS**
RIVIT.IT