




ITEM TECHNICAL CARD

| | |
|--------------------|-------------|
| height (mm) | 1,25 |
| hole diameter (mm) | 8,483/8,271 |
| E (mm) | 6,647 |
| B (mm) | 9,624 |
| Diameter | M8 |
| C (5H) mm | 8,886/8,812 |
| C (6H) mm | 8,912/8,812 |
| D (4H) mm | 7,288/7,188 |
| D (5H) mm | 7,313/7,188 |

| | | | | | | | | |
|---|-------|--|--|---|---|---|--|-------------------------|
| DESCRIZIONE \ DESCRIPTION: ELIRIV-Stainless st. self-locking helicoid (15082) M8x1,25 | | | | CATEGORIA \ CATEGORY: | | 1875400 | | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | |  FASTENERS & TOOLS  RIVIT.IT | | |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: | | | | | |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW | | | | | |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: 1 OF 1 | FORMATO FOGLIO: SHEET FORMAT: A4 | METODO 1 (ISO 128) METHOD 1 (ISO 128) | | | REVISIONE: REVISION: |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT Mod.P023_07 |  | | | |