


ITEM TECHNICAL CARD



length (mm)	40,0
Material	white zinc plated steel 8.8
Diameter	M20
UNI	5739
DIN	933
ISO	4017
k (mm)	12,5
Rules Description	hex cap screws fully threaded
s (mm)	30,0
e min (mm)	35,53
pitch	2,5

DESCRIZIONE \ DESCRIPTION: <b>Hex head bolt UNI 5739/DIN 933 8.8 - white zinc plated steel M20x40</b>		CATEGORIA \ CATEGORY: <b>20160ZB.00050</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	REVISIONE: REVISION:
		FOGLIO \ SHEET: <b>1 OF 1</b>	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
		FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT