



ITEM TECHNICAL CARD

s (mm)	5,0
length (mm)	12
Material	plain steel 10.9
Diameter	M8
UNI	5933
DIN	7991
ISO	10642
D (mm)	16,0
k (mm)	4,4
t (mm)	3,5
Rules Description	hexagon socket countersunk head screws partially/fully threaded
pitch	1,25

DESCRIZIONE \ DESCRIPTION:		CATEGORIA \ CATEGORY:		22009GR.00200	
Hex socket countersunk head screw U5933/D7991 10.9 - plain steel					
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY:	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale:		
<b>RIVIT</b>			General surface roughness:		
CONTROLLATO DA \ CHECKED BY:	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]:	<b>NON SCALARE IL DISEGNO</b>		
<b>RIVIT</b>		HEAT TREATMENT (SURF) DEPTH [mm]:	<b>DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY:	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET:	FORMATO FOGLIO:	METODO 1 (ISO 128)
<b>RIVIT</b>			<b>1 OF 1</b>	<b>A4</b>	METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT	REVISIONE: REVISION:
				<b>Mod.P023_07</b>	