


ITEM TECHNICAL CARD

|                   |   |
|-------------------|---|
| s (mm)            | 10,0  |
| length (mm)       | 25,0  |
| Material          | plain steel 10.9  |
| Diameter          | M16   |
| UNI               | 5933  |
| DIN               | 7991  |
| ISO               | 10642   |
| D (mm)            | 30,0  |
| k (mm)            | 7,5   |
| t (mm)            | 5,3   |
| Rules Description | hexagon socket countersunk head screws partially/fully threaded |
| pitch             | 2,0   |

|   |       |  |   |
|---|-------|--|---|
| DESCRIZIONE \ DESCRIPTION:<br><b>Hex socket countersunk head screw U5933/D7991 10.9 - plain steel</b> |       | CATEGORIA \ CATEGORY:<br><b>22069GR</b>  |   |
| MATERIAL \ MATERIAL:  |       | TRATTAMENTO TERMICO \ HEAT TREATMENT:  | NOTE \ NOTES:   |
| ESEGUITO DA \ DRAWN BY:<br><b>RIVIT</b>   | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT:   | Rugosità superficiale generale:<br>General surface roughness:                         |
| CONTROLLATO DA \ CHECKED BY:<br><b>RIVIT</b>  | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]:<br>HEAT TREATMENT (SURF) DEPTH [mm]: | <b>NON SCALARE IL DISEGNO<br/>DO NOT RESIZE THE DRAW</b>                              |
| APPROVATO DA \ APPROVED BY:<br><b>RIVIT</b>   | DATA: | DUREZZA \ HARDNESS:  | METODO 1 (ISO 128)<br>METHOD 1 (ISO 128)  |
|   |       | FOGLIO \ SHEET:<br><b>1 OF 1</b>   | REVISIONE:<br>REVISION:   |
|   |       | PESO \ WEIGHT:   | CARTIGLIO \ FORMAT<br><b>Mod.P023_07</b>  |
|   |       | Scale \ SCALE:   |  |



**FASTENERS  
& TOOLS**  
RIVIT.IT