


ITEM TECHNICAL CARD

s (mm)	10,0
length (mm)	50,0
Material	plain steel 10.9
Diameter	M16
UNI	5933
DIN	7991
ISO	10642
D (mm)	30,0
k (mm)	7,5
t (mm)	5,3
Rules Description	hexagon socket countersunk head screws partially/fully threaded
pitch	2,0

DESCRIZIONE \ DESCRIPTION: <b>Hex socket countersunk head screw U5933/D7991 10.9 - plain steel</b>		CATEGORIA \ CATEGORY: <b>22074GR.00050</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	REVISIONE: REVISION:
		FOGLIO \ SHEET: <b>1 OF 1</b>	
		FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	
		CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT