


ITEM TECHNICAL CARD

s (mm)	10,0
length (mm)	55,0
Material	white zinc plated steel 10.9
Diameter	M16
UNI	5933
DIN	7991
ISO	10642
D (mm)	30,0
k (mm)	7,5
t (mm)	5,3
Rules Description	hexagon socket countersunk head screws partially/fully threaded
pitch	2,0

DESCRIZIONE \ DESCRIPTION: Hex socket countersunk head screw U5933/D7991 10.9 -				CATEGORIA \ CATEGORY: 22075ZB.00050	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT