


ITEM TECHNICAL CARD

| | |
|-------------------|---|
| s (mm) | 10,0 |
| length (mm) | 90 |
| Material | plain steel 10.9 |
| Diameter | M16 |
| UNI | 5933 |
| DIN | 7991 |
| ISO | 10642 |
| D (mm) | 30,0 |
| k (mm) | 7,5 |
| t (mm) | 5,3 |
| Rules Description | hexagon socket countersunk head screws partially/fully threaded |
| pitch | 2,0 |

| | | | |
|---|-------|--|---|
| DESCRIZIONE \ DESCRIPTION: Hex socket countersunk head screw U5933/D7991 10.9 - plain steel | | CATEGORIA \ CATEGORY: 22079GR | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | NOTE \ NOTES: |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | METODO 1 (ISO 128) METHOD 1 (ISO 128) |
| | | FOGLIO \ SHEET: 1 OF 1 | REVISIONE: REVISION: |
| | | PESO \ WEIGHT: | CARTIGLIO \ FORMAT Mod.P023_07 |
| | | Scale \ SCALE: |  |



**FASTENERS
& TOOLS**
RIVIT.IT