

ITEM TECHNICAL CARD



T - head width (mm)	16,0
L - rivet nuts lenght (mm)	16,0
k - head thickness (mm)	1,3
grip range (mm)	0,4 ÷ 2,8
max clamping torque (Nm)	5,9 ÷ 9,9
d - rivet nut pitch	M6
hole diameter	12,8 ÷ 13,0
Hardness (Nm)	60
body material	EPDM
head type	dome

DESCRIZIONE \ DESCRIPTION: NPTC-Prensert EPDM Brass Anti-chatter gr0,4-4,0 8 DH M6		CATEGORIA \ CATEGORY: 2395000.01500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		FOGLIO \ SHEET: 1 OF 1	REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:
		CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT