

ITEM TECHNICAL CARD



T - head width (mm)	27,0
L - rivet nuts lenght (mm)	80,0
k - head thickness (mm)	1,3
grip range (mm)	38,0 ÷ 64,0
max clamping torque (Nm)	59,0 ÷ 69,0
d - rivet nut pitch	M12
hole diameter	24,1 ÷ 24,3
Hardness (Nm)	60
body material	EPDM
head type	dome

DESCRIZIONE \ DESCRIPTION: <b>NPTC-Prensert EPDM Brass Anti-chatter gr38,0-6 4,0 DH M12</b>		CATEGORIA \ CATEGORY: <b>2395900.00025</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	
		FOGLIO \ SHEET: <b>1 OF 1</b>	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
		FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	



**FASTENERS & TOOLS**  
RIVIT.IT