



ITEM TECHNICAL CARD

hole diameter (mm)	6,8
lockbolt diameter (mm)	6,4
T - head width (mm)	13,4
L - bolt length (mm)	67,0
K - head thickness (mm)	4,0
shear strenght (N)	5300
model	RGAT08-20
tensile strenght (N)	7200
grip range (mm)	8,0 ÷ 32,0

DESCRIZIONE \ DESCRIPTION: RIVLOCKGRIP-Lockbolt Aluminium d.6,4 gr 8,0-32, 0 DH RGAT 8-20				CATEGORIA \ CATEGORY:		2492800		
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:		 FASTENERS & TOOLS  RIVIT.IT		
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:					
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW					
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)			REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	