


ITEM TECHNICAL CARD



hole diameter (mm)	4,1
d - rivet diameter	4,0
T - head width (mm)	8,0
L - rivet length (mm)	8,0
k - head thickness (mm)	1,7
shear strength (N)	1800
tensile strength (N)	2500
grip range (mm)	3,5 ÷ 5,0
body material	copper
mandrel material	steel
head type	dome

DESCRIZIONE \ DESCRIPTION: SRFT-Sealed blind rivet Copper/Steel DH 4,0x8,0				CATEGORIA \ CATEGORY: 2591400.01000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT