


ITEM TECHNICAL CARD



hole diameter (mm)	9,3 - 9,6
diameter (mm)	M6
model	RSCFFL060
L - length (mm)	12
minimum hole depth (mm)	15,0
A x h (mm)	10,0 x 1,25
a x h (mm)	6,0 x 1,0

DESCRIZIONE \ DESCRIPTION: RSCF-F-Self tapping socketGalv. Steel w/hole f.10 M6x1x12 - 0318L		CATEGORIA \ CATEGORY: 2791200	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	REVISIONE: REVISION:
		FOGLIO \ SHEET: 1 OF 1	CARTIGLIO \ FORMAT Mod.P023_07
		FORMATO FOGLIO: SHEET FORMAT: A4	



**FASTENERS
& TOOLS**
RIVIT.IT