



ITEM TECHNICAL CARD

hole diameter (mm)	8,2 - 8,4
lockbolt diameter (mm)	8,0
T - head width (mm)	16,7
L1 - lockbolt length (mm)	52,0
L2 (mm)	18,2 - 19,8
K - head thickness (mm)	5,2
shear strenght (N)	13000
model	RLAT10-04
tensile strenght (N)	12500
grip range (mm)	3,2 ÷ 9,5

DESCRIZIONE \ DESCRIPTION: RIVLOCK-Lockbolt Aluminium DH d.8 gr 3,2-9,5 RLAT 10-4 d8				CATEGORIA \ CATEGORY: 2892200	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		 FASTENERS & TOOLS  RIVIT.IT
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	