

ITEM TECHNICAL CARD



hole diameter (mm)	8,2 - 8,4
lockbolt diameter (mm)	8,0
T - head width (mm)	16,7
L1 - lockbolt length (mm)	63,0
L2 (mm)	27,9 - 29,6
K - head thickness (mm)	5,2
shear strenght (N)	29800
model	RLFT10-11
tensile strenght (N)	26700
grip range (mm)	14,3 ÷ 20,6

DESCRIZIONE \ DESCRIPTION: <b>RIVLOCK-Lockbolt Steel DH d.8,0 gr 14,3-20,6 RLFT 10-11 d8</b>			CATEGORIA \ CATEGORY: <b>3023400</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	
		PESO \ WEIGHT:	Scale \ SCALE:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
			CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	REVISIONE: REVISION:



**FASTENERS  
& TOOLS**  
RIVIT.IT