


ITEM TECHNICAL CARD

hole diameter (mm)	3,97 ÷ 4,04
d - rivet diameter	4,0
T - head width (mm)	8,0
L - rivet length (mm)	6,9
number of pieces in cartridge (pz)	38
k - head thickness (mm)	1,0
shear strength (N)	1090
tensile strength (N)	1620
grip range (mm)	3,7 ÷ 4,9
body material	aluminium
head type	dome
RAL	RAL9005

DESCRIZIONE \ DESCRIPTION: BRAT9005-Speedriv Alu RAL9005 in cartridge 38pcs D gr 3,7-5,0				CATEGORIA \ CATEGORY: 3241600.17000	
MATERIALE \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT