



ITEM TECHNICAL CARD

s (mm)	4,0
C (mm)	1,2
D (mm)	13,6
length (mm)	14
Material	plain steel 10.9
Diameter	M6
k (mm)	3,3
pitch	1,0

DESCRIZIONE \ DESCRIPTION: <b>Hex socket flange button head screw ISO7380-2 10.9 - plain steel</b>		CATEGORIA \ CATEGORY: <b>44202GR</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FUOGIO \ SHEET: <b>1 OF 1</b>
		PESO \ WEIGHT:	FORMATO FOGGIO: <b>A4</b>
		Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
			METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
			 <b>FASTENERS &amp; TOOLS</b>  <b>RIVIT.IT</b>