


ITEM TECHNICAL CARD

air consumption x cycle 6 bar (lt)	5,0
air working pressure (bar)	6,0
min/max air pressure (bar)	5 - 7
weight (kg)	2,1
noise level dB(A)	< 76,0
vibrations (m/s <sup>2</sup> )	< 2,5
power (N)	19.000
max stroke (mm)	6,5
motor speed spin on (rpm)	2450
motor speed spin off (rpm)	2850

DESCRIZIONE \ DESCRIPTION: <b>RIV938P-Hydrop. tool for rivet nuts in a box, with strengthened engine</b>				CATEGORIA \ CATEGORY: <b>4439600</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT