


ITEM TECHNICAL CARD

cylinder stroke (mm)	32
max power at 6bar (N)	40000
hoses length (m)	3
min/max air pressure (bar)	5 - 7
nominal air pressure (bar)	6
oil pressure (6 bar air pressure) (bar)	300
intensification ratio	1:50
noise level dB(A)	< 80
vibrations (m/s ²)	< 2,5
handle weight without kit (kg)	1,7
total weight (kg)	28
booster dimensions (WxDxH) (mm)	49,5x39,5x25,0

DESCRIZIONE \ DESCRIPTION: RIV511B-Hydroprn. tool blind bolt,struct.riv.MT3 supplied without kit				CATEGORIA \ CATEGORY: 45961RT	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT