


ITEM TECHNICAL CARD

length (mm)	18
Material	yellow zinc plated steel C15
Diameter	4,5
DIN	7505A
Rules Description	flat head chipboard screws
D min/max (mm)	8,64/9,00
K max (mm)	2,55
r1~ (mm)	2,2
b max (mm)	1,3
N Pozi Recess	2
recess m ~	4,8

DESCRIZIONE \ DESCRIPTION: Flat head chipboard screw DIN 7505A yellow zinc plated steel C15		CATEGORIA \ CATEGORY: 46038ZG	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		FOGLIO \ SHEET: 1 OF 1	REVISIONE: REVISION:
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT Mod.P023_07
		Scale \ SCALE:	



**FASTENERS
& TOOLS**
RIVIT.IT