

ITEM TECHNICAL CARD

diámetro vite	M6
E (mm)	0,5
tipo	DGF4106G
A (mm)	14,0
C (mm)	7,1
B (mm)	12,4
s - spessore lamiera (mm)	2,0 - 2,1
D (mm)	20,4
foro lamiera (mm)	8,0x13,0

DESCRIZIONE \ DESCRIPTION:					CATEGORIA \ CATEGORY:		5125100.01000		
DG4106-G Dado FE Gab.c/Al.OX ss2,0-2,1 f 8,0x13 M6									
MATERIAL \ MATERIAL:			TRATTAMENTO TERMICO \ HEAT TREATMENT:				NOTE \ NOTES:		
ESEGUITO DA \ DRAWN BY: RIVIT		DATA:	TRATT. SUPERFICIALE\ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:				
CONTROLLATO DA \ CHECKED BY: RIVIT		DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:			NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
APPROVATO DA \ APPROVED BY: RIVIT		DATA:	DUREZZA \ HARDNESS:	FOGLIO\ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT:	A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	
			PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07				



FASTENERS
& TOOLS

RIVIT.IT