




ITEM TECHNICAL CARD

s (mm)	4,0
C (mm)	1,2
D (mm)	13,6
length (mm)	30
Material	plain steel 10.9
Diameter	M6
k (mm)	3,3
pitch	1,0

DESCRIZIONE \ DESCRIPTION: Hex socket flange button head screw ISO7380-2 10.9 - plain steel		CATEGORIA \ CATEGORY: 51522GR	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FUOGIO \ SHEET: 1 OF 1
		PESO \ WEIGHT:	Scale \ SCALE: Mod.P023_07
			FORMATO FOGGIO: A4 SHEET FORMAT: METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
			
		 FASTENERS & TOOLS  RIVIT.IT	