


ITEM TECHNICAL CARD



T - head width (mm)	12,0
L1 - shank length (mm)	12,5
L2 - shank length after fixing (mm)	7,0
L - rivet nuts length (mm)	15,0
k - head thickness (mm)	1,5
grip range (mm)	1,0 ÷ 3,0
axial proof load for thread (N)	28000
max clamping torque (Nm)	30
d - rivet nut pitch	M8
hole diameter	9,9
body material	steel
head type	dome
shank type	knurled cylindrical

DESCRIZIONE \ DESCRIPTION: RIVBOLT-BFTCZ Blind bolt steel zp knurled h.9,9 grip 1,0-3,0mm		CATEGORIA \ CATEGORY: 5356700.00250	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		FUOGGIO \ SHEET: 1 OF 1	REVISIONE: REVISION:
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT Mod.P023_07
		Scale \ SCALE:	



**FASTENERS
& TOOLS**
RIVIT.IT