


ITEM TECHNICAL CARD

A (mm)	4,5
TX	25
length (mm)	40,0
Material	white zinc plated steel 4.8
Diameter	M5
pitch	0,8
ISO	14583
k (mm)	3,7
t (mm)	1,91
Rules Description	socket head cap tapping screw cut off pin
d1 (mm)	9,5

DESCRIZIONE \ DESCRIPTION: <b>Vite TC Torx T25 ISO 14583/DIN 7985 4.8 ZB M5x40</b>				CATEGORIA \ CATEGORY: <b>54299ZB.00200</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT