

ITEM TECHNICAL CARD

s (mm)	3,0
length (mm)	6
Material	stainless steel A4
Diameter	M5
UNI	5933
DIN	7991
ISO	10642
D (mm)	10,0
k (mm)	2,8
t (mm)	2,3
Rules Description	hexagon socket countersunk head screws partially/fully threaded
pitch	0,8

DESCRIZIONE \ DESCRIPTION:		CATEGORIA \ CATEGORY:		5572600.00500	
Hex socket countersunk head screw U5933/D7991 A4 - stainless steel					
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY:	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale:		
RIVIT			General surface roughness:		
CONTROLLATO DA \ CHECKED BY:	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]:	NON SCALARE IL DISEGNO		
RIVIT		HEAT TREATMENT (SURF) DEPTH [mm]:	DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY:	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET:	FORMATO FOGLIO:	METODO 1 (ISO 128)
RIVIT			1 OF 1	A4	METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT	REVISIONE: REVISION:
				Mod.P023_07	



FASTENERS & TOOLS
 RIVIT.IT